

# Tyfo® VG Dash Coat

## for the Tyfo® Advanced Fire Protection (AFP) System

### DESCRIPTION

Tyfo® VG Dash Coat is the second component of the specialized Tyfo® AFP System.

### USE

To promote the adhesion of Tyfo® VG or other fireproofing material to the substrate. (See Tyfo® VG Data Sheet for additional information).

### ADVANTAGES

- UL listed, Design No. N790 and X842

### COVERAGE

One 48-lb. bag of mixed material should cover approximately 900 sq. ft. of surface area when applied as specified under the "Application" section of this data sheet.

### PACKAGING

Tyfo® VG Dash Coat is packaged in 48-lb. bags.

### SHELF LIFE

Two years in properly stored conditions.

### STORAGE CONDITIONS

Store bags in dry place, palletized off the ground, if possible. Cover with polyethelene sheeting to protect from moisture.

### CERTIFICATE OF COMPLIANCE

- Will be supplied upon request, complete with state and federal packaging laws with copy of labels used.
- Material safety data sheets will be supplied upon request.

### HOW TO USE

#### Tyfo® VG Dash Coat

### INSTALLATION

Tyfo® System to be installed by Fyfe Co. LLC trained and certified applicators. Installation shall be in strict compliance with the Fyfe Co. LLC Quality Control Manual.

### APPLICATION

Apply the Tyfo® VG Dash Coat within 15 -30 minutes of the Tyfo® VG Primer. Tyfo® VG Dash Coat shall be spray-applied. Add minimum amount of water that allows material to pass through spray gun. Spray material in a non-continuous spatter pattern at an approximate rate of one (1) 48-lb. bag per 900 sq. ft. of area surface (approx. 1/16" thick).

Do not mix more material than can be used within the 30 minute set time.

Do not fully coat surface. The exposed surface shall be approximately 10% to 30% of the application area.

Allow approximately 4 hours of set time of Tyfo® VG Dash Coat prior to application of Tyfo® VG.

### LIMITATIONS

Minimum application temperature of the material is 40° F (4° C).

### CAUTION!

### FIRST AID

In case of skin contact, wash thoroughly with soap and water. For eye contact, flush immediately with plenty of water; contact physician immediately. For respiratory problems, remove to fresh air. Wash clothing before reuse.

### CLEANUP

Tools may be cleaned with water. Clean promptly after use. Dried or hardened material is difficult to remove. Pour the contaminated water over the ground or suitable absorbents to dry then dispose of in approved waste containers.

### SHIPPING LABELS CONTAIN

- State specification number with modifications, if applicable
- Component designation
- Type, if applicable
- Manufacturer's name
- Date of manufacture
- Batch name
- State lot number, if applicable
- Directions for use
- Warnings or precautions required by law

**NOT FOR INTERNAL CONSUMPTION.  
CONSULT MATERIAL SAFETY DATA SHEET  
(MSDS) FOR MORE INFORMATION.  
KEEP OUT OF REACH OF CHILDREN.  
FOR INDUSTRIAL USE ONLY.**

### MATERIAL PROPERTIES

Color	Gray
Pot Life	~30 minutes

## Fyfe Co. LLC

Tyfo® Fibrwrap® Systems  
Nancy Ridge Technology Center  
6310 Nancy Ridge Drive, Suite 103, San Diego, CA 92121  
Tel: 858.642.0694 Fax: 858.642.0947  
E-mail: [info@fyfeco.com](mailto:info@fyfeco.com) Web: <http://www.fyfeco.com>

**Statement of Responsibility:** The technical information and application advice in this publication is based on the present state of our best scientific and practical knowledge. As the nature of the information herein is general, no assumption can be made as to the product's suitability for a particular use or application, and no warranty as to its accuracy, reliability or completeness, either expressed or implied, is given other than those required by State legislation. The owner, his representative or the contractor is responsible for checking the suitability of products for their intended use. Field service, where provided, does not constitute supervisory responsibility. Suggestions made by the Fyfe Co., either verbally or in writing, may be followed, modified or rejected by the owner, engineer or contractor since they, and not the Fyfe Co., are responsible for carrying out procedure appropriate to a specific application.